



Range of Products >> Terminal Block >> Spring & Lighting TB >> GSL034-02P MORE >



**Catalogue**

- Terminal Block**
  - Spring & Lighting Terminal block
  - Wire-Protector Terminal block
  - Screw-Clamp Terminal block
  - Pluggable Terminal block
  - Barrier Terminal block
  - Transformer Terminal block
  - Feed-through / Fuse Terminal block
  - Interface Mould Housing
  - UK /MK Din-Rail Terminal block
  - Ws Din-Rail Terminal block
  - Ceramic & Fix Terminal block
  - Terminals & Components
- Connector**
  - D-Sub Series
  - Pin Header & Socket
  - Box Header & Ejector
  - IC socket / Sip socket / Zip socket
  - USB Connectors
  - Dip Switch Series
  - Wire / Board to board connector
  - Round Connector
- Telecommunication & Network**
  - Cables Series
  - PCB Jack
  - Keystone Jack
  - Face Plate
  - Patch adaptor & Patch cord
  - Patch Panel
  - Telephone Accessory
  - Communication Accessory
  - Tools & Tester
- Test Probes**

Standard	UL	IEC
Rated voltage	300V	400V
Rated current	20A	24A
Wire range	24-12AWG	0.75-2.5mm <sup>2</sup>
Withstanding voltage	AC2500V/1Min	
Ambient temperature	-40°C~+105°C	
Strip length	8-9mm	
Pitch	-----	
Poles	2P	
Housing	PA66+5%GF,UL94V-0	
Pin header	Phosphor Bronze	
Wire guard	Stainless steel	



Copyright: **NINGBO GOSUN TECHNOLOGY CO.,LTD** Add: Xiaolin Industry zone, Xiaolin Town,Cixi,Ningbo,China,315321  
 Tel: 0086-574-63506685 Fax: 0086-574-63989953 E-mail: gosun@gosun-tech.com / info@gosun-tech.com